

item number	A	B	C	max. number of inserted cables			weight	
				Ø6	Ø8	Ø10		
	mm	mm	mm	pcs	pcs	pcs	kg/pc	
<b>SD 2_PO</b>	49	32	79	50	38	25	0,54	🔥
<b>SD 4_PO</b>	33,5	32	57	25	19	12	0,33	🔥

product description: The group holder is suitable for fastening cable or cable bundles to the wall or ceiling.

The holder is fixed to the base material with a concrete screw or other suitable anchoring elements.

The holder allows the installation of cables with different diameters.

The construction of the group holders enables easy addition of more cables to the route.

The maximum load capacity of the holder is 6 kg/m. It is recommended to install the holders with a spacing of 300-600 mm, depending also on the rigidity of the cables.

Distance between holders (mm)	300	400	500	600
Max. recommended load of the holder (kg)	6	4,5	3,6	3

surface finish: PO - Pre-Galvanized according to EN 10346, EN 10143, zinc-layer 15-27 µm

sales amount: á 1 pc

classification 🔥: ČSN 73 0895 P 90-R  
 DIN 4102-12 E 90  
 STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

Classification is identical to SD 2\_S group holders

🔥 products approved for non-standard constructions

storage: EN 60721-3-1

